


BSPP 60° CONE O-RING FEMALE SWIVEL - 90°

BS5200 / ISO 12151-6


HF1P-WS 4SP-R12 - BSPP OR FS 90

HF1P-4SH/R13/R15 -12 -16 - BSPP OR FS 90


35502902



35502901



35502903



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	dash	dn	inch	dash	inch	thread	lc mm	lc inch	ld mm	ld inch	h1 mm	h2 mm
35502902-060600	-06	DN 10	3/8"	-06	3/8"	33/8" X 19	33.2	1.31	36	1.42	-	22
35502902-060800	-06	DN 10	3/8"	-08	1/2"	1/2" X 14	33.2	1.31	35.5	1.4	-	27
35502902-080800	-08	DN 12	1/2"	-08	1/2"	1/2" X 14	37.2	1.46	40.5	1.59	-	27
35502902-081000	-08	DN 12	1/2"	-10	5/8"	5/8" X 14	37.6	1.48	43	1.69	-	27
35502902-081200	-08	DN 12	1/2"	-12	3/4"	3/4" X 14	37.8	1.49	40.9	1.61	-	32
35502901-101000	-10	DN 16	5/8"	-10	5/8"	5/8" X 14	49.4	1.94	46	1.81	-	27
35502902-101200	-10	DN 16	5/8"	-12	3/4"	3/4" X 14	50.7	2	48.9	1.93	-	32
35502901-121200	-12	DN 19	3/4"	-12	3/4"	3/4" X 14	57	2.24	55	2.17	-	32
35502902-121600	-12	DN 19	3/4"	-16	1"	1" X 11	56.2	2.21	53.4	2.1	-	38
35502901-161600	-16	DN 25	1"	-16	1"	1" X 11	72.7	2.86	70	2.76	-	41
35502902-162000	-16	DN 25	1"	-20	1.1/4"	1.1/4" X 11	71.9	2.83	71	2.8	-	50
35502903-202000	-20	DN 32	1.1/4"	-20	1.1/4"	1.1/4" X 11	87.1	3.43	89	3.5	-	50
35502902-202400	-20	DN 32	1.1/4"	-24	1.1/2"	1.1/2" X 11	86.4	3.4	83	3.27	-	55
35502903-242400	-24	DN 38	1.1/2"	-24	1.1/2"	1.1/2" X 11	108.1	4.26	102.8	4.05	-	55
35502903-323200	-32	DN 51	2"	-32	2"	2" X 11	129.1	5.08	123	4.84	-	70