


ORFS FEMALE SWIVEL - 90° - SHORT DROP


SAE J516 / ISO 12151-1

HF2P-MT - ORFS FS 90 SD

110319S2



110319S1



ITEM CODE	HOSE ID			TERMINATION			DIMENSIONS					
	dash	dn	inch	dash	tube inch	thread	lc mm	lc inch	ld mm	ld inch	h1 mm	h2 mm
110319S2-040400	-04	DN 06	1/4"	-04	1/4"	9/16" X 18	29.1	1.15	21	0.83	-	17
110319S2-040600	-04	DN 06	1/4"	-06	3/8"	11/16" X 16	29.1	1.15	23.5	0.93	-	22
110319S2-050600	-05	DN 08	5/16"	-06	3/8"	11/16" X 16	32.3	1.27	24	0.94	-	22
110319S1-060600	-06	DN 10	3/8"	-06	3/8"	11/16" X 16	33.1	1.3	25	0.98	-	22
110319S1-060800	-06	DN 10	3/8"	-08	1/2"	13/16" X 16	33.1	1.3	28	1.1	-	24
110319S1-080800	-08	DN 12	1/2"	-08	1/2"	13/16" X 16	36.5	1.44	34	1.34	-	24
110319S2-081000	-08	DN 12	1/2"	-10	5/8"	1" X 14	40.5	1.59	37	1.46	-	30
110319S1-101000	-10	DN 16	5/8"	-10	5/8"	1" X 14	46.1	1.81	40	1.57	-	30
110319S2-101200	-10	DN 16	5/8"	-12	3/4"	1.3/16" X 12	46.1	1.81	41.5	1.63	-	36
110319S1-121000	-12	DN 19	3/4"	-10	5/8"	1" X 14	45.9	1.81	40	1.57	-	30
110319S1-121200	-12	DN 19	3/4"	-12	3/4"	1.3/16" X 12	52.1	2.05	43.5	1.71	-	36
110319S2-121600	-12	DN 19	3/4"	-16	1"	1.7/16" X 12	52.1	2.05	44	1.73	-	41
110319S1-161200	-16	DN 25	1"	-12	3/4"	1.3/16" X 12	56.9	2.24	43.5	1.71	-	36
110319S2-161600	-16	DN 25	1"	-16	1"	1.7/16" X 12	66.5	2.62	57	2.24	-	41
110319S2-162000	-16	DN 25	1"	-20	1.1/4"	1.11/16" X 12	66.5	2.62	57	2.24	-	50
110319S2-202000	-20	DN 32	1.1/4"	-20	1.1/4"	1.11/16" X 12	80.9	3.19	69	2.72	-	50
110319S2-202400	-20	DN 32	1.1/4"	-24	1.1/2"	2" X 12	80.9	3.19	69	2.72	-	60
110319S2-242400	-24	DN 38	1.1/2"	-24	1.1/2"	2" X 12	93.8	3.69	77	3.03	-	60