

PH276 - TRIFLEX



Construction

- Inner tube** Black colour, synthetic rubber resistant to oil
- Reinforcement** Three high tensile steel braids
- Cover** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish*
- Application** High pressure for forest industry. Compatible with mineral, vegetable oils, glycol, polyglycol based, synthetic ester based oils, oils in water emulsion

Cover Options
PH276: MSHA

Item Code	Dash Size	DN	ID		RI OD		OD		WP		BP		BR/r		W	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH276-06	-06	10	3/8	9.5	0.70	17.7	0.84	21.3	7250	500	29000	2000	7.1	180	0.832			
PH276-08	-08	12	1/2	12.7	0.81	20.5	0.96	24.3	6815	470	27260	1880	9.1	230	1.017			
PH276-10	-10	16	5/8	16.0	0.96	24.4	1.10	28.0	5945	410	23780	1640	9.8	250	1.199			
PH276-12	-12	19	3/4	19.0	1.09	27.8	1.24	31.5	5440	375	21750	1500	11.8	300	1.457			
PH276-16	-16	25	1	25.4	1.37	34.7	1.52	38.7	4570	315	18270	1260	13.4	340	1.902			



Temperature Range : Continuous: -40°C to +100°C

Intermittent : +120°C

*Smooth cover available only upto size 1"