

**PH279 - R15**

**Applicable Standard :** SAE J517 -100R15 / ISO 3862



**Construction**

- Inner tube** Black colour, Synthetic rubber resistant to oil and water
- Reinforcement** Four high tensile steel wire spiral (DN19-25)\$ Six high tensile steel wire spiral (DN31-51)
- Cover** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone
- Application** 420 bar super high pressure Hydraulic Lines and hydrostatic transmission lines. Also, suitable for impulse surge lines with more life cycles for use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Earthmoving equipment and machineries / systems

Cover Options	
PH279 :	MSHA
PH259 :	ABRAZONX MSHA

**Note :** 5/8" & 2" Not covered under SAE 100R15

Item Code	Dash Size	DN	ID		RI OD		OD		WP		BP		BR/r		W kg/m	Packaging		
			inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm		Qty (ft)	Type	No of sections
PH279-06	-06	10	3/8	9.8	0.69	17.5	0.84	21.4	6000	420	24000	1680	3.5	90	0.822		Reel	1
PH279-08	-08	12	1/2	13.1	0.80	20.4	0.82	24.6	6000	420	24000	1680	4.5	115	0.994		Reel	1
PH279-10	-10	16	5/8	16.2	0.97	24.6	1.06	27.0	6000	420	24000	1680	4.7	120	1.258		Reel	1
PH279-12	-12	19	3/4	19.2	1.14	29.0	1.25	31.7	6090	420	24360	1680	10.5	265	1.814		Reel	1
PH279-16	-16	25	1	25.7	1.40	35.6	1.51	38.3	6090	420	24360	1680	13.0	330	2.277		Reel	1
PH279-20	-20	31	1.1/4	32.2	1.85	47.0	1.94	49.4	6090	420	24360	1680	17.5	445	4.269		Reel	1
PH279-24	-24	38	1.1/2	38.5	2.17	55.1	2.28	58.0	6090	420	24360	1680	20.9	530	5.747		Reel	1
PH279-32	-32	51	2	51.2	2.68	68.0	2.85	72.5	6090	420	24360	1680	23.6	600	8.217		Reel	1

**Packaging Dimensions**

Core	Flange	Height



**Temperature Range :** Continuous: -40°C to +121°C

**Impulse Cycles :** 500,000 cycles