

### PH280 - WATER BLAST 30



### Construction

- Inner tube**                      Black colour, Synthetic rubber resistant to oil and water
- Reinforcement**              Four high tensile steel wire spirals
- Cover**                              Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone
- Application**                      Water blasting, Water jetting, cleaning equipment. Delivery of water and water emulsions

| Cover Options |
|---------------|
| PH280 : MSHA  |

| Item Code | Dash Size | DN | ID   |      | RI OD |      | OD   |      | WP    |     | BP    |      | BR/r  |     | W     |
|-----------|-----------|----|------|------|-------|------|------|------|-------|-----|-------|------|-------|-----|-------|
|           |           |    | inch | mm   | inch  | mm   | inch | mm   | psi   | bar | psi   | bar  | inch  | mm  | kg/m  |
| PH280-04  | -04       | 06 | 1/4  | 6.4  | 0.58  | 14.7 | 0.70 | 17.9 | 12325 | 850 | 30815 | 2125 | 5.12  | 130 | 0.627 |
| PH280-06  | -06       | 10 | 3/8  | 9.5  | 0.69  | 17.5 | 0.83 | 21.1 | 12325 | 850 | 30815 | 2125 | 6.10  | 155 | 0.838 |
| PH280-08  | -08       | 12 | 1/2  | 12.7 | 0.84  | 21.3 | 0.97 | 24.6 | 12325 | 850 | 30815 | 2125 | 7.87  | 200 | 1.184 |
| PH280-12  | -12       | 19 | 3/4  | 19.0 | 1.17  | 29.8 | 1.29 | 32.8 | 12325 | 850 | 30815 | 2125 | 9.84  | 250 | 2.024 |
| PH280-16  | -16       | 25 | 1    | 25.4 | 1.38  | 35.1 | 1.51 | 38.3 | 12325 | 850 | 30815 | 2125 | 11.81 | 300 | 2.447 |



**Temperature Range** : Continuous: -40°C to +90°C