

PH282 - WATER BLAST 45



Construction

- Inner tube** Black colour, Synthetic rubber resistant to oil and water
- Reinforcement** Four high tensile steel wire spirals
- Cover** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone
- Application** Water blasting, Water jetting, cleaning equipment. Delivery of water and water emulsions

| Cover Options |
|---------------|
| PH282 : MSHA |

| Item Code | Dash Size | DN | ID | | RI OD | | OD | | WP | | BP | | BR/r | | W kg/m | Qty (ft) | Type | No of sections |
|-----------|-----------|----|------|------|-------|------|------|------|-------|------|-------|------|------|-----|-----------|----------|------|----------------|
| | | | inch | mm | inch | mm | inch | mm | psi | bar | psi | bar | inch | mm | | | | |
| PH282-06 | -06 | 10 | 3/8 | 9.5 | 0.71 | 18.0 | 0.81 | 20.6 | 18125 | 1250 | 45315 | 3125 | 6.1 | 155 | 0.967 | | | |
| PH282-08 | -08 | 12 | 1/2 | 12.7 | 0.63 | 23.4 | 1.14 | 29.0 | 18125 | 1250 | 45315 | 3125 | 9.1 | 230 | 2.048 | | | |



Temperature Range : Continuous: -40°C to +90°C