

PH344 / PH345 - HIGH PRESSURE PAINT SPRAY



Construction

Inner tube	Polyamide
Reinforcement	One or more braids of Synthetic Fiber with anti-static polymeric layer
Cover	Polyurethane, Blue Colour
Application	Airless paint spray systems for 228 to 360 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Specially suitable for pulsating electric piston pumps

Note : Factory made hose assemblies of PH344-4 available with UL mark. Approval can be seen @www.ul.com; Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m			
PH344-03	-03	05	3/16	4.8	0.413	10.5	3500	240	14000	960	3.5	88	95			
PH344-04	-04	06	1/4	6.4	0.520	13.2	3300	228	13200	912	4.0	100	131			
PH344-06	-06	10	3/8	9.5	0.690	17.5	3300	228	13200	912	5.0	125	241			
PH344-08	-08	12	1/2	12.7	0.890	22.6	3300	228	13200	912	7.0	175	351			
PH345-03	-03	05	3/16	4.8	0.435	11.0	5200	360	15600	1080	3.5	88	110			
PH345-04	-04	06	1/4	6.4	0.520	13.2	5200	360	15600	1080	4.1	104	145			
PH345-06	-06	10	3/8	9.5	0.730	18.5	3600	250	14400	1000	5.1	130	270			



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids