

PH471 - STEAM 1 W/B

Applicable Standard : IS 10655 Type 2/ISO 6134 Type 1A/BS 5342 Type 1A



Construction

Inner tube	Black colour, EPDM rubber resistant to high temperature steam
Reinforcement	Single steel wire Braid
Cover	Red Colour, EPDM rubber resistant to abrasion, heat and weather
Application	High temperature steam Lines at constant pressure of 145 psi

Note : Black Colour Cover also available

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH471-06	-06	10	3/8	10.0	0.69	17.5	145	10	1450	100	5.1	130	0.399
PH471-08	-08	12	1/2	12.5	0.87	22.0	145	10	1450	100	5.9	150	0.496
PH471-12	-12	19	3/4	19.0	1.14	29.0	145	10	1450	100	9.1	230	0.727
PH471-16	-16	25	1	25.4	1.37	34.8	145	10	1450	100	11.8	300	0.800
PH471-20	-20	32	1.1/4	31.5	1.65	42.0	145	10	1450	100	14.8	375	1.281



Temperature Range : Continuous: Up to +185°C Steam