

**PH514 - PW 4K - 1 WB**

**Construction**

<b>Inner tube</b>	Black colour, Synthetic rubber resistant to hot water
<b>Reinforcement</b>	Single steel wire braid
<b>Cover</b>	Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish*
<b>Application</b>	For pressure washer applications with a maximum pressure of 280 Bar. For cold and hot water up to 155 °C

**Note :** Also Available in Blue and Grey colour Covers on request, Not suitable for steam and oil applications

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W			
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m	Qty (ft)	Type	No of sections
PH514-04	-04	06	1/4	6.7	0.47	12.0	4000	280	12000	830	1.4	35	0.194			
PH514-05	-05	08	5/16	8.2	0.54	13.7	4000	280	12000	830	2.6	65	0.235			
PH514-06	-06	10	3/8	9.8	0.63	16.0	4000	280	12000	830	3.0	75	0.305			
PH514-08	-08	12	1/2	13.1	0.77	19.6	4000	280	12000	830	3.9	100	0.425			



**Temperature Range :** Continuous: -10°C to +155°C

\*Smooth cover available only upto size 1"