

PH521 - SUPER SERVICE HOSE

Applicable Standard : Exceeds EN 857 - 1SC / EN 1829-

2



Construction

Inner tube	Black colour, Synthetic rubber resistant to hot water
Reinforcement	Single steel wire braid
Cover	Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish*, Color option in Grey, Blue available on request
Application	Cleaning lines for lobby and semi professional machines. High flexibility for use with minerals, glycols, polyglycols oils, synthetic ester oils, oils in water emulsion

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		kg/m	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH521-04	-04	06	1/4	6.7	0.47	12.0	5220	360	13050	900	3.0	75	0.195			
PH521-05	-05	08	5/16	8.2	0.54	13.6	4930	340	12325	850	3.3	85	0.232			
PH521-06	-06	10	3/8	9.8	0.63	16.0	4350	300	10875	750	3.5	90	0.312			
PH521-08	-08	12	1/2	13.1	0.78	19.6	3625	250	9065	625	5.1	130	0.428			



Temperature Range : Continuous: -40°C to +155°C

*Smooth cover available only upto size 1"