

PH531 - FUEL HOSE

Applicable Standard : SAE J30 R2 TYPE 2



Construction

- Inner tube** Black colour, Synthetic rubber resistant to oil and fuel
- Reinforcement** Textile reinforcement
- Cover** Black Colour, Synthetic rubber resistant to oil, ozone. Available in Wrap and Smooth finish*
- Application** Low Pressure coupled and uncoupled low-permeation Fuel hose for Automotive and allied application, Physical, Extrac table and fuel permeation properties as specified in SAE J30 - R2 - Type 2 standard for use with gasoline, diesel fuel, lubrication oil, or the vapour present in either fuel system or in crank case of internal combustion engines.

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W kg/m	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH531-03	-03	05	3/16	4.76	0.53	13.5	145	10	725	50	2.0	50	0.131			
PH531-04	-04	06	1/4	6.35	0.59	15.1	145	10	725	50	2.6	65	0.155			
PH531-05	-05	08	5/16	7.94	0.66	16.7	145	10	725	50	3.0	75	0.180			
PH531-06	-06	10	3/8	9.53	0.72	18.2	145	10	725	50	3.0	75	0.193			
PH531-08	-08	12	1/2	12.7	0.84	21.4	145	10	725	50	3.9	100	0.314			
PH531-10	-10	16	5/8	15.88	0.97	24.6	145	10	510	35	4.9	125	0.370			
PH531-12	-12	19	3/4	19.05	1.09	27.8	145	10	510	35	5.9	150	0.454			



Temperature Range : Continuous: -40°C to +100°C

*Smooth cover available only upto size 1"