

PH609 - THERMOPLASTIC LINED PAINT S & D HOSE 10 BAR



Construction

Inner tube	Black colour, Synthetic rubber with Thermoplastic liner
Reinforcement	Plies of synthetic textile cords with steel helix and two cross antistatic copper wires
Cover	Black synthetic rubber resistant to ozone, weather and abrasion
Application	For suction and conveying paint and allied chemicals

Item Code	Dash Size	ID		OD		WP		BP		V	W	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar	bar	kg/m			
PH609-08	-08	1/2	12.0	0.87	22.0	150	10	450	30	0.90	0.45			
PH609-12	-12	3/4	19.0	1.22	31.0	150	10	450	30	0.90	0.69			
PH609-16	-16	1	25.0	1.46	37.0	150	10	450	30	0.90	0.85			
PH609-20	-20	1.1/4	32.0	1.73	44.0	150	10	450	30	0.90	1.10			
PH609-24	-24	1.1/2	38.0	1.97	50.0	150	10	450	30	0.90	1.20			
PH609-32	-32	2	51.0	2.48	63.0	150	10	450	30	0.90	1.60			



Temperature Range : Continuous: -40°C to +80°C