

PH617 - OIL FUEL DELIVERY HOSE - 20 BAR



Construction

Inner tube	Black colour, Synthetic rubber resistant to oil
Reinforcement	Plies of synthetic textile cords and two cross and static copper wires
Cover	Black colour, Synthetic rubber resistant to oil, ozone and abrasion
Application	Mandrel built oil discharge hose for handling grades of gasoline or petroleum oils of aromatic content upto 50% in dispensing station etc, during winter/summer seasons

Item Code	Dash Size	ID		OD		WP		BP		W	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar				
PH617-12	-12	3/4	19.0	1.06	27.0	300	20	870	60	0.68			
PH617-16	-16	1	25.0	1.38	35.0	300	20	870	60	0.81			
PH617-20	-20	1.1/4	32.0	1.65	42.0	300	20	870	60	1.22			
PH617-24	-24	1.1/2	38.0	1.89	48.0	300	20	870	60	1.35			
PH617-32	-32	2	51.0	2.44	62.0	300	20	870	60	2.04			
PH617-40	-40	2.1/2	63.0	2.95	75.0	300	20	870	60	2.65			
PH617-48	-48	3	76.0	3.46	88.0	300	20	870	60	3.08			
PH617-56	-56	3.1/2	89.0	4.09	104.0	300	20	870	60	3.60			
PH617-64	-64	4	102.0	4.57	116.0	300	20	870	60	4.87			
PH617-80	-80	5	127.0	5.59	142.0	300	20	870	60	5.60			
PH617-96	-96	6	152.0	6.54	166.0	300	20	870	60	7.00			



Temperature Range : Continuous: -20°C to +80°C