

PH620 - AIR & WATER DISCHARGE HOSE - 10 BAR



Construction

Inner tube	Black colour, Synthetic rubber resistant to oil
Reinforcement	Plies of synthetic textile cords
Cover	Black colour, Synthetic rubber resistant to oil, ozone and abrasion
Application	Light weight hose designed for air, water & dust delivery in underground mines

Item Code	Dash Size	ID		OD		WP		BP		kg/m	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar				
PH620-16	-16	1	25.0	1.26	32.0	150	10	435	30	0.48			
PH620-20	-20	1.1/4	32.0	1.54	39.0	150	10	435	30	0.62			
PH620-24	-24	1.1/2	38.0	1.77	45.0	150	10	435	30	0.80			
PH620-32	-32	2	51.0	2.28	58.0	150	10	435	30	0.94			
PH620-40	-40	2.1/2	63.0	2.76	70.0	150	10	435	30	1.20			
PH620-48	-48	3	76.0	3.27	83.0	150	10	435	30	1.50			
PH620-56	-56	3.1/2	89.0	3.82	97.0	150	10	435	30	1.70			
PH620-64	-64	4	102.0	4.29	109.0	150	10	435	30	2.20			
PH620-80	-80	5	127.0	5.39	137.0	150	10	435	30	3.80			
PH620-96	-96	6	152.0	6.38	162.0	150	10	435	30	4.50			
PH620-128	-128	8	203.0	8.54	217.0	150	10	435	30	6.10			



Temperature Range : Continuous: -25°C to +70°C