

PH621 - CEMENT / PLASTER PLACEMENT HOSE



Construction

Inner tube	Black colour, Synthetic and natural rubber blend resistant to abrasion
Reinforcement	Plies of synthetic textile cords
Cover	Black colour, Synthetic rubber resistant to ozone, weather and abrasion
Application	For Cement/ Plaster/ Sand placement in construction industry

Item Code	Dash Size	ID		OD		WP		BP		W	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar				
PH621-16	-16	1	25.0	1.46	37.0	150	10	435	30	0.70			
PH621-20	-20	1.1/4	32.0	1.81	46.0	150	10	435	30	0.99			
PH621-24	-24	1.1/2	38.0	2.05	52.0	150	10	435	30	1.42			
PH621-32	-32	2	51.0	2.56	65.0	150	10	435	30	2.04			
PH621-40	-40	2.1/2	64.0	3.15	80.0	150	10	435	30	2.65			
PH621-48	-48	3	76.0	3.62	92.0	150	10	435	30	3.11			
PH621-64	-64	4	102.0	4.65	118.0	150	10	435	30	4.57			
PH621-80	-80	5	127.0	5.79	147.0	150	10	435	30	6.29			
PH621-96	-96	6	152.0	6.93	176.0	150	10	435	30	9.40			
PH621-128	-128	8	203.0	9.09	231.0	150	10	435	30	14.40			



Temperature Range : Continuous: -30°C to +70°C