

PH624 - SHOT BLASTING HOSE W.P. 12 BAR - PH2



Construction

- Inner tube** Black colour, Synthetic and natural rubber blend resistant to abrasion
- Reinforcement** Plies of synthetic textile cords with two cross antistatic copper wires
- Cover** Black colour, Synthetic rubber resistant to ozone, weather and abrasion
- Application** Suitably designed long lasting heavy duty hose for use in sand, metal grits and foundry waste with conductive rubber compound to ensure static electricity dissipation abrasion loss of the tube according to ISO 4649: 50+5mm3

Cover Options
PH674-PH1 : Premium abrasion

Item Code	Dash Size	ID		OD		WP		BP		kg/m	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar				
PH624-08	-08	1/2	12.7	1.06	27.0	175	12	525	36	0.61			
PH624-12	-12	3/4	19.0	1.34	34.0	175	12	525	36	0.80			
PH624-16	-16	1	25.0	1.57	40.0	175	12	525	36	0.97			
PH624-20	-20	1.1/4	32.0	1.89	48.0	175	12	525	36	1.32			
PH624-24	-24	1.1/2	38.0	2.13	54.0	175	12	525	36	1.45			
PH624-32	-32	2	51.0	2.87	73.0	175	12	525	36	2.20			
PH624-40	-40	2.1/2	64.0	3.35	85.0	175	12	525	36	3.26			
PH624-48	-48	3	76.0	3.94	100.0	175	12	525	36	3.90			
PH624-64	-64	4	102.0	4.96	126.0	175	12	525	36	4.40			



Temperature Range : Continuous: -30°C to +70°C