

PH639 - BULK MATERIAL DISCHARGE - 20 BAR



Construction

Inner tube	Black colour, Synthetic and natural rubber blend resistant to abrasion
Reinforcement	Plies of synthetic textile cords
Cover	Black colour, Synthetic Rubber resistant to ozone, weather and abrasion
Application	For Discharge of bulk material dry cement, gravel, sand etc., in Construction Industry

Item Code	Dash Size	 ID		 OD		 WP		 BP		 W				
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m				
PH639-32	-32	2	51.0	2.64	67.0	300	20	870	60	1.70		Qty (ft)	Type	No of sections
PH639-40	-40	2.1/2	64.0	3.11	79.0	300	20	870	60	2.10				
PH639-48	-48	3	76.0	3.70	94.0	300	20	870	60	2.60				
PH639-64	-64	4	102.0	4.80	122.0	300	20	870	60	4.40				
PH639-80	-80	5	127.0	5.75	146.0	300	20	870	60	5.70				
PH639-96	-96	6	152.0	6.77	172.0	300	20	870	60	7.00				
PH639-128	-128	8	203.0	9.05	230.0	300	20	870	60	9.00				



Temperature Range : Continuous: -30°C to +70°C