

PH646 - EPDM CHEMICAL SUCTION & DISCHARGE HOSE



Construction

- Inner tube** Black colour, EPDM synthetic rubber resistant to wide range of industrial chemicals
- Reinforcement** Plies of synthetic textile cords with steel helix and two cross anti static copper wires
- Cover** Black colour, Synthetic rubber resistant to ozone, weather and abrasion
- Application** For conveying wide range of light chemicals

Item Code	Dash Size	ID		OD		WP		BP		W	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m			
PH646-08	-08	1/2	12.7	0.97	24.7	250	17	750	51	0.56			
PH646-12	-12	3/4	19.0	1.22	31.0	250	17	750	51	0.68			
PH646-16	-16	1	25.0	1.46	37.0	250	17	750	51	0.80			
PH646-20	-20	1.1/4	32.0	1.73	44.0	250	17	750	51	0.99			
PH646-24	-24	1.1/2	38.0	2.05	52.0	250	17	750	51	1.50			
PH646-32	-32	2	51.0	2.64	67.0	250	17	750	51	2.04			
PH646-40	-40	2.1/2	64.0	3.15	80.0	250	17	750	51	2.70			
PH646-48	-48	3	76.0	3.62	92.0	250	17	750	51	3.12			
PH646-64	-64	4	102.0	4.65	118.0	250	17	750	51	4.60			



Temperature Range : Continuous: -30°C to +120°C