

PH649 - CONCRETE DELIVERY HOSE



Construction

- Inner tube** Black colour, Synthetic and natural rubber blend resistant to abrasion
- Reinforcement** Plies of synthetic textile cords with two cross anti static copper wires
- Cover** Black colour, Synthetic rubber resistant to ozone, weather and abrasion
- Application** Designed for concrete pumping in construction industry

Item Code	Dash Size	ID		OD		WP		BP		kg/m	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar				
PH649-20	-20	1.1/4	32.0	1.93	49.0	1235	85	2465	170	1.60			
PH649-24	-24	1.1/2	38.0	2.20	56.0	1235	85	2465	170	1.80			
PH649-32	-32	2	51.0	2.80	71.0	1235	85	2465	170	3.00			
PH649-40	-40	2.1/2	64.0	3.43	87.0	1235	85	2465	170	3.77			
PH649-48	-48	3	76.0	4.02	102.0	1235	85	2465	170	4.90			
PH649-56	-56	3.1/2	88.0	4.53	115.0	1235	85	2465	170	5.66			
PH649-64	-64	4	102.0	5.20	132.0	1235	85	2465	170	7.36			
PH649-80	-80	5	127.0	6.18	157.0	1235	85	2465	170	8.92			



Temperature Range : Continuous: -30°C to +70°C