

PH657 - OIL FUEL DELIVERY HOSE FRAS - 20 BAR



Construction

Inner tube	Black colour, Conductive Synthetic Rubber resistant to oil
Reinforcement	Plies of synthetic textile cords
Cover	Black colour, Conductive Synthetic rubber resistant to weather and abrasion
Application	Mandrel built heavy duty oil delivery hose for handling a wide range of gasoline or petroleum oils of aromatic content up to 50% from tank truck, in dispensing station, refineries, etc.

Item Code	Dash Size	 ID		 OD		 WP		 BP		 W	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m			
PH657-12	-12	3/4	19.0	1.22	31.0	300	20	870	60	0.68			
PH657-16	-16	1	25.0	1.46	37.0	300	20	870	60	0.81			
PH657-20	-20	1.1/4	32.0	1.73	44.0	300	20	870	60	1.22			
PH657-24	-24	1.1/2	38.0	2.01	51.0	300	20	870	60	1.35			
PH657-32	-32	2	51.0	2.60	66.0	300	20	870	60	2.04			
PH657-40	-40	2.1/2	63.0	3.11	79.0	300	20	870	60	2.65			
PH657-48	-48	3	76.0	3.58	91.0	300	20	870	60	3.08			
PH657-56	-56	3.1/2	89.0	4.17	106.0	300	20	870	60	3.60			
PH657-64	-64	4	102.0	4.72	120.0	300	20	870	60	4.87			
PH657-80	-80	5	127.0	5.75	146.0	300	20	870	60	5.60			
PH657-96	-96	6	152.0	6.69	170.0	300	20	870	60	7.00			



Temperature Range : Continuous: -20°C to +80°C