

PH663 - AIR & WATER DISCHARGE HOSE FRAS - 20 BAR



Construction

Inner tube	Black colour, Conductive synthetic rubber resistant to air and water
Reinforcement	Plies of synthetic textile cord
Cover	Black colour, Conductive Synthetic rubber resistant to air and water
Application	Hose designed for Air, water & stone dust delivery in underground mines

Item Code	Dash Size	ID		OD		WP		BP		W	Qty (ft)	Type	No of sections
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m			
PH663-16	-16	1	25.0	1.34	34.0	300	20	900	60	0.53			
PH663-20	-20	1.1/4	32.0	1.65	42.0	300	20	900	60	0.84			
PH663-24	-24	1.1/2	38.0	1.89	48.0	300	20	900	60	0.98			
PH663-32	-32	2	51.0	2.44	62.0	300	20	900	60	1.10			
PH663-40	-40	2.1/2	63.0	2.99	76.0	300	20	900	60	1.50			
PH663-48	-48	3	76.0	3.50	89.0	300	20	900	60	1.72			
PH663-56	-56	3.1/2	89.0	4.06	103.0	300	20	900	60	2.10			
PH663-64	-64	4	102.0	4.57	116.0	300	20	900	60	2.40			
PH663-80	-80	5	127.0	5.59	142.0	300	20	900	60	3.00			
PH663-96	-96	6	152.0	6.57	167.0	300	20	900	60	5.00			
PH663-128	128	8	203.0	8.62	219.0	300	20	900	60	7.20			



Temperature Range : Continuous: -20°C to +85°C