

## PH130 - R3 TEMP MASTER MSHA

Applicable Standard : Exceeds SAE J517 - 100R3



### Construction

- Inner tube** Synthetic rubber - black resistant to oil and water
- Reinforcement** Double textile braids
- Cover** Synthetic rubber - black resistant to abrasion, weather, oil & ozone
- Application** Hoses for use with petroleum and water base hydraulic fluids. Suitable for agricultural, Earth moving, construction & material handling equipments under elevated temperatures

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH130-06	-06	10	3/8	9.6	0.75	19	1160	80	4570	315	3.9	100	0.331
PH130-08	-08	12	1/2	12.9	0.94	23.8	1015	70	4060	280	4.9	125	0.49
PH130-10	-10	16	5/8	16.1	1.06	27.0	945	65	3555	245	5.5	140	0.615
PH130-12	-12	19	3/4	19.2	1.25	31.8	800	55	3045	210	5.9	150	0.758
PH130-16	-16	25	1	25.6	1.48	37.6	580	40	2320	160	8.1	205	0.857
PH130-20	-20	31	1.1/4	32.1	1.73	44.0	435	30	1525	105	9.8	250	1.089



Temperature Range : -40°C to +135°C