

**PH133 - TRACK SAFE - R13**



**Applicable Standard :** SAE J517 - 100R13 / EN 856 - R13/ ISO 3862 / EN 45545-2

**Construction**

- Inner tube** Synthetic rubber resistant to oil and water
- Reinforcement** Four high tensile steel wire spiral (DN19-25)\$ Six high tensile steel wire spiral (DN31-51)
- Cover** Synthetic rubber resistant to abrasion, weather, oil & ozone.
- Application** 350 bar super high pressure Hydraulic Lines and hydrostatic transmission lines. Also, suitable for impulse surge lines with more life cycles for use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Earthmoving equipment and machineries / systems. Hose meets hazard level HL1 & HL2 of R22 & R23. The specific fire-retardant cover minimizes the release of toxic substances & better visibility in case of fire. This compliance is crucial to enhance passenger safety and prevent the spread of fire within railway vehicles.

Item Code	Dash Size	DN	ID		RI OD		OD		WP		BP		BR/r		W kg/m	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH133-12	-12	19	3/4	19.2	1.14	29.0	1.26	32.1	5075	350	20300	1400	9.45	240	1.814			
PH133-16	-16	25	1	25.7	1.40	35.6	1.52	38.7	5075	350	20300	1400	11.81	300	2.277			
PH133-20	-20	31	1.1/4	32.2	1.85	47.0	1.96	49.8	5075	350	20300	1400	16.54	420	4.269			
PH133-24	-24	38	1.1/2	38.5	2.17	55.1	2.26	57.3	5075	350	20300	1400	19.69	500	5.747			
PH133-32	-32	51	2	51.4	2.67	67.7	2.80	71.1	5075	350	20300	1400	25.20	640	7.852			



**Temperature Range :** Continuous: -40°C to +121°C

**Impulse Cycles :** 500,000 cycles