

PH182 - LIFT MASTER HARDX MSHA

Applicable Standard : ISO 18752 - AC



Construction

- Inner tube** Synthetic rubber - black resistant to oil and water
- Reinforcement** Single steel wire braid
- Cover** HardX black, Extra abrasion, oil and ozone resistant synthetic rubber. Available in wrap & smooth finish
- Application** Compact 250 bar hose for forklift hydraulic with tight bend radius and abrasion resistant cover for durable performance in confined spaces.

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH182-04	-04	06	1/4	6.7	0.48	12.3	3625	250	14500	1000	1.4	35	0.207			
PH182-05	-05	08	5/16	8.2	0.55	14.0	3625	250	14500	1000	1.6	40	0.259			
PH182-06	-06	10	3/8	9.8	0.61	15.5	3625	250	14500	1000	1.6	40	0.307			
PH182-08	-08	12	1/2	13.1	0.76	19.4	3625	250	14500	1000	2.0	50	0.440			



Temperature Range : Continuous: -40°C to +100°C

Impulse Cycles : 200,000