

PH194 - LOW TEMPERATURE - R18

Applicable Standard : SAE 100R18 / DIN EN ISO 394



Construction

- Inner tube** Thermoplastic Elastomer
- Reinforcement** One or more Braids of Synthetic Fiber
- Cover** Special Polyester Elastomer, Black Colour, Pin pricked.
- Application** Constant Pressure Hydraulic Lines 210 bar. Suitable for hydraulic application with low temperature requirements and abrasion resistance for use with petroleum, synthetic or water based fluids in hydraulic systems. Suitable for agricultural machinery, earthmoving, cold storage material handling equipment and systems. Also suitable for industrial gases and other applications. Please consult manufacturer

Other Options
PH195 : Electrical non conductive application, Orange colour cover

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH194-03	-03	05	3/16	4.8	0.405	10.3	3000	210	12000	840	1.2	30	80
PH194-04	-04	06	1/4	6.4	0.490	12.4	3000	210	12000	840	1.8	45	120
PH194-05	-05	08	5/16	8.0	0.560	14.2	3000	210	12000	840	2.0	50	153
PH194-06	-06	10	3/8	9.5	0.650	16.6	3000	210	12000	840	3.0	75	188
PH194-08	-08	12	1/2	12.7	0.890	22.5	3000	210	12000	840	3.5	90	298
PH194-10	-10	16	5/8	16.0	1.060	25.4	3000	210	12000	840	4.7	120	370
PH194-12	-12	20	3/4	19.0	1.170	29.7	3000	210	12000	840	6.0	150	435
PH194-16	-16	25	1	25.4	1.560	39.6	3000	210	12000	840	10.0	250	600



Temperature Range : Continuous: -55°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids