

PH295 - R19

Applicable Standard : SAE J517 - 100R19



Construction

Inner tube	Synthetic rubber - black resistant to oil and water
Reinforcement	Single or Double steel wire braids
Cover	Synthetic rubber - Black resistant to abrasion, weather, oil & ozone.
Application	Compact constant pressure hydraulic lines 280 bar for use with petroleum, synthetic or water based fluids in hydraulic systems. Suitable for Agricultural, Construction & Material handling equipments / systems

Cover Options

PH295 : MSHA
PH229 : HARDX MSHA
PH222 : ABRAZONX MSHA

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		kg/m	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH295-04	-04	06	1/4	6.7	0.47	12.0	4060	280	16240	1120	2.0	50	0.186			
PH295-05	-05	08	5/16	8.2	0.59	14.9	4060	280	16240	1120	2.2	55	0.366			
PH295-06	-06	10	3/8	9.8	0.67	17.1	4060	280	16240	1120	2.6	65	0.466			
PH295-08	-08	12	1/2	13.1	0.80	20.4	4060	280	16240	1120	3.5	90	0.624			
PH295-10	-10	16	5/8	16.2	0.94	24.0	4060	280	16240	1120	3.9	100	0.745			
PH295-12	-12	19	3/4	19.3	1.09	27.7	4060	280	16240	1120	4.7	120	0.901			
PH295-16	-16	25	1	25.7	1.40	35.8	4060	280	16240	1120	5.9	150	1.603			



Temperature Range : Continuous: -40°C to +100°C

Intermittent : +121°C

Impulse Cycles : 200,000 cycles