

PH301 - SEWER JET - 2500 PSI



Construction

- Inner tube** Thermoplastic Elastomer
- Reinforcement** One or more Braids of Synthetic Fiber
- Cover** Polyurethane, Orange Colour

Application Standard Sewer cleaning vehicles and cleaning equipments. Special construction for optimum cut and wear resistance with bonded tube and cover. Available in long lengths with a special cover resistant to microbiological degradation light weight compared to Conventional rubber alternatives and increased lifetime

Note : * Single braid of steel wire#Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH301-03	-03	05	3/16	4.8	0.413	10.5	2500	175	6250	438	1.6	40	83			
PH301-04	-04	06	1/4	6.4	0.505	12.8	2500	175	6250	438	1.6	40	118			
PH301-06	-06	10	3/8	9.5	0.640	16.3	2500	175	6250	438	2.4	60	167			
PH301-08	-08	12	1/2	12.7	0.810	20.6	2500	175	6250	438	4.0	100	248			
PH301-10	-10	16	5/8	16.0	1.030	26.2	2500	175	6250	438	4.3	110	417			
PH305-12	-12	20	3/4	19.0	1.160	29.5	2800	190	7000	475	4.7	120	440			
PH305-16	-16	25	1	25.4	1.460	37.1	2800	190	7000	475	5.9	150	650			
PH305-20	-20	32	1.1/4	31.8	1.840	46.7	2800	190	7000	475	9.8	250	985			
PH301W-03*	-03	05	3/16	4.8	0.366	9.30	4350	300	17400	1200	1.2	30	120			



Temperature Range : Continuous: -40°C to +60°C