

PH326 / PH327 / PH328 - BEVERAGE DISPENSING HOSE



Construction

- Inner tube** Thermoplastic Elastomer food quality and FDA approved
- Reinforcement** PH326 Single or double braid of synthetic fiber\$ PH327 Single braid of steel wire\$ PH328 Single braid of aramid fiber
- Cover** Polyurethane, Black Colour, Pin Pricked
- Application** High pressure beverage dispensing lines 210 to 420 bar Specifically designed for gases, also gas mixtures used in fixed and mobile beverage dispensing units. Special tube material flavour free eliminates contamination risks and conforms to FDA and EC regulations. Please contact for different and working pressure

Note : Grey Colour Cover also available

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m			
PH326-04	-04	06	1/4	6.4	0.490	12.4	3000	210	12000	840	1.4	35	114			
PH326-06	-06	10	3/8	9.5	0.640	16.3	3000	210	12000	840	2.4	60	170			
PH326-08	-08	12	1/2	12.7	0.855	21.7	3000	210	12000	840	3.9	100	300			
PH327-03	-03	05	3/16	4.8	0.380	9.7	5000	350	20000	1400	1.6	40	141			
PH327-04	-04	06	1/4	6.4	0.460	11.7	4650	320	18600	1280	1.8	45	182			
PH328-02	-02	03	1/8	3.2	0.320	8.1	6000	420	24000	1680	1.0	25	57			
PH328-03	-03	05	3/16	4.8	0.405	10.3	5000	350	20000	1400	1.0	25	87			
PH328-04	-04	06	1/4	6.4	0.490	12.4	5000	350	20000	1400	1.3	32	118			
PH328-08	-08	12	1/2	12.7	0.770	19.6	5000	350	20000	1400	3.0	77	225			



Temperature Range : Continuous: -40°C to +80°C