

PH341 - PAINT & AGGRESSIVE CHEMICAL SPRAY - 1W

Construction

Inner tube	PTFE (Polytetrafluoroethylene)
Reinforcement	Single Braid of steel wire
Cover	Polyurethane, Blue Colour, Pin pricked
Application	Airless paint spray systems for 200 to 350 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Specially suitable for moisture cure adhesives and two components chemicals transfer

Note : Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W			
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m	Qty (ft)	Type	No of sections
PH341-03	-03	05	3/16	4.8	0.380	9.7	5000	350	20000	1400	1.2	30	138			
PH341-04	-04	06	1/4	6.4	0.460	11.7	4650	320	18600	1280	1.6	40	180			
PH341-05	-05	08	5/16	8.0	0.535	13.6	4000	275	16000	1100	2.0	50	220			
PH341-06	-06	10	3/8	9.5	0.595	15.1	3600	250	14400	1000	2.4	60	257			
PH341-08	-08	12	1/2	12.7	0.725	18.4	2900	200	11600	800	3.0	75	337			



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids