

PH358 - R7 COMPACT HOSE



Construction

- Inner tube** Thermoplastic Elastomer
- Reinforcement** One or more Braids of Synthetic Fiber
- Cover** Polyurethane, Black Colour, Pin pricked
- Application** Medium pressure hydraulic lines 230 bar. Suitable for hydraulic application with increased resistance to abrasion for use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, Articulating & Telescopic booms and material handling equipment

Note : Available Twin & Multi line with different Hose combination and size. Also special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH358-03	-03	05	3/16	4.8	0.394	10.0	3335	230	11600	800	1.8	45	88
PH358-04	-04	06	1/4	6.4	0.454	11.5	3335	230	11600	800	2.0	50	92
PH358-05	-05	08	5/16	8.0	0.560	14.2	3335	230	11600	800	2.4	60	135
PH358-06	-06	10	3/8	9.5	0.630	16.0	3335	230	11600	800	3.1	80	150
PH358-08	-08	12	1/2	12.7	0.855	21.7	2900	200	11600	800	3.9	100	280



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids