

**PH365L - AIR / WATER - LIGHT DUTY**



**Construction**

- Inner tube** Plasticized PVC, Black
- Reinforcement** Single braid of Synthetic fiber
- Cover** Abrasion resistant thermo-compound, black Colour
- Application** Specially designed for Tyre inflation, light engineering industry and general purpose air line

**Note :** Special colours available on request

| Item Code | Dash Size | DN | ID   |      | OD    |      | WP  |     | BP  |     | BR/r |     | W   |
|-----------|-----------|----|------|------|-------|------|-----|-----|-----|-----|------|-----|-----|
|           |           |    | inch | mm   | inch  | mm   | psi | bar | psi | bar | inch | mm  | g/m |
| PH365L-04 | -04       | 06 | 1/4  | 6.5  | 0.453 | 11.5 | 230 | 16  | 920 | 64  | 2.4  | 60  | 90  |
| PH365L-05 | -05       | 08 | 5/16 | 8.0  | 0.530 | 13.5 | 230 | 16  | 920 | 64  | 3.3  | 85  | 130 |
| PH365L-06 | -06       | 10 | 3/8  | 9.5  | 0.590 | 15.0 | 230 | 16  | 920 | 64  | 4.3  | 110 | 150 |
| PH365L-08 | -08       | 12 | 1/2  | 12.7 | 0.736 | 18.7 | 230 | 16  | 920 | 64  | 5.1  | 130 | 220 |
| PH365L-12 | -12       | 19 | 3/4  | 19.0 | 1.024 | 26.0 | 145 | 10  | 580 | 40  | 5.7  | 145 | 330 |
| PH365L-16 | -16       | 25 | 1    | 25.4 | 1.240 | 31.5 | 145 | 10  | 580 | 40  | 6.7  | 170 | 450 |



**Temperature Range :** Continuous: -10°C to +60°C