

PH460 ROCKDRILL



Construction

Inner tube	Black colour, synthetic rubber resistant to air.
Reinforcement	Single steel wire braid
Cover	Black colour, synthetic rubber resistant to weather, abrasion & ozone.
Application	Compressed air service in severe working conditions in mines, quarries and industrial applications

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W kg/m	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH 460-08	-08	12	1/2	13.1	0.79	20	1160	80	3480	240	7.87	200	0.385			
PH 460-12	-12	19	3/4	19.3	1.14	29	870	60	2610	180	9.45	240	0.675			
PH 460-16	-16	25	1	25.9	1.4	35.5	725	50	2175	150	11.81	300	0.777			
PH 460-20	-20	31	1.1/4	32.4	1.65	42	725	50	2175	150	16.54	420	0.976			
PH 460-24	-24	38	1.1/2	38.7	2.04	51.7	600	40	1740	120	19.69	500	1.337			
PH 460-32	-32	51	2	51.3	2.48	63	600	40	1740	120	24.8	630	1.783			



Temperature Range : Continuous: -40°C to +90°C

*Smooth cover available only upto size 1"