

PH482 - STEAM 2 W/B

Applicable Standard : Exceeds ISO 6134 TYPE 2B



Construction

Inner tube	Black colour, EPDM rubber resistant to high temperature steam
Reinforcement	Double steel wire Braids
Cover	Red cover, EPDM rubber resistant to oil, heat and weather. Black colour option available on request
Application	High temperature steam Lines at constant pressure of 290 psi

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W W	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH482-06	-06	10	3/8	10.0	0.77	19.5	260	18	2610	180	5.1	130	0.421			
PH482-08	-08	12	1/2	12.5	0.91	23.0	260	18	2610	180	5.9	150	0.589			
PH482-12	-12	19	3/4	19.0	1.18	30.0	260	18	2610	180	9.1	230	0.846			
PH482-16	-16	25	1	25.4	1.45	36.8	260	18	2610	180	11.8	300	1.095			
PH482-20	-20	32	1.1/4	31.5	1.71	43.5	260	18	2610	180	14.8	375	1.505			
PH482-24	-24	38	1.1/2	38.0	1.95	49.5	260	18	2610	180	17.9	455	1.780			
PH482-32	-32	51	2	51.0	2.52	64.0	260	18	2610	180	23.6	600	2.261			
PH482-40	-40	63	2.1/2	63.0	3.27	83.0	260	18	2610	180	26.6	675	4.214			
PH482-48	-48	76	3	76.0	3.86	98.0	260	18	2610	180	28.5	725	4.962			



Temperature Range : Continuous: Up to +230°C Steam