

PH684 - SHOT BLASTING HOSE W.P. 12 BAR



Construction

Inner tube	Black Colour, Synthetic and natural rubber blend resistant to abrasion
Reinforcement	Four Plies of synthetic textile cords with two cross anti static copper wires
Cover	Black colour, Synthetic rubber resistant to ozone, weather and abrasion
Application	Suitably designed long lasting heavy duty hose for use in sand , metal grits and foundry waste with conductive rubber compound to ensure static electricity dissipation abrasion loss of the tube according to ISO 4649: 50+5mm3

Item Code	Dash Size	ID		OD		WP		BP		kg/m
		inch	mm	inch	mm	psi	bar	psi	bar	
PH684-08	-08	1/2	12.7	1.18	30.0	175	12	525	36	0.75
PH684-12	-12	3/4	19.0	1.50	38.0	175	12	525	36	1.10
PH684-16	-16	1	25.0	1.89	48.0	175	12	525	36	1.60
PH684-20	-20	1.1/4	32.0	2.17	55.0	175	12	525	36	1.90
PH684-24	-24	1.1/2	38.0	2.40	61.0	175	12	525	36	2.15
PH684-32	-32	2	51.0	2.87	73.0	175	12	525	36	2.65



Temperature Range : Continuous: -30°C to +70°C