

PH761 - HYBRID HOSE - 1W



Construction

Inner tube	Thermoplastic Elastomer
Reinforcement	Single Braid of Steel Wire
Cover	Synthetic Rubber, Black Colour
Application	Medium Pressure Hydraulic Lines 88 to 225 bar. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, material handling equipment and machineries / systems

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W g/m	Qty (ft)	Type	No of sections
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm				
PH761-04	-04	06	1/4	6.4	0.500	12.7	3260	225	13100	900	2.0	50	197			
PH761-06	-06	10	3/8	9.5	0.660	16.8	2610	180	10500	720	2.5	64	281			
PH761-08	-08	12	1/2	12.7	0.770	19.6	2320	160	9300	640	3.5	90	367			
PH761-12	-12	20	3/4	19.0	1.050	26.7	1520	105	6100	420	5.0	125	579			
PH761-16	-16	25	1	25.4	1.250	31.8	1270	88	5100	352	10.0	250	720			



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids