

## PH804 - POLY - FUEL HOSE

Applicable Standard: EN 13765 TYPE 2: 2010



## Construction

Construction Hose made from Polypropylene fabric and films with PVC coated fabric cover, Inner & Outer wire

is galvanised mild steel

**Colour** Yellow with white strip

**Application** Suction and discharge hose mainly for transfer of petroleum products by Road tankers and Rail

tankers and loading gantries

| Item<br>Code | Dash<br>Size | ID ID |       | DOD OD |       | WP  |     | BR/r  |     |          |      |                |
|--------------|--------------|-------|-------|--------|-------|-----|-----|-------|-----|----------|------|----------------|
| Oode         | Oize         | inch  | mm    | inch   | mm    | psi | bar | inch  | mm  | Qty (ft) | Туре | No of sections |
| PH804-16     | -16          | 1     | 25.0  | 1.26   | 32.0  | 150 | 10  | 4.92  | 125 |          |      |                |
| PH804-24     | -24          | 1-1/2 | 38.0  | 1.97   | 50.0  | 150 | 10  | 5.91  | 150 |          |      |                |
| PH804-32     | -32          | 2     | 51.0  | 2.40   | 61.0  | 150 | 10  | 7.87  | 200 |          |      |                |
| PH804-40     | -40          | 2-1/2 | 63.0  | 2.99   | 76.0  | 150 | 10  | 7.87  | 200 |          |      |                |
| PH804-48     | -48          | 3     | 76.0  | 3.46   | 88.0  | 150 | 10  | 11.02 | 280 |          |      |                |
| PH804-64     | -64          | 4     | 102.0 | 4.41   | 112.0 | 150 | 10  | 15.75 | 400 |          |      |                |



Temperature Range: Continuous: -30°C to +80°C