

PH819 - POLY - CHEMICAL HEAVY DUTY HOSE - SG

Applicable Standard : EN 13765 Type 3



Construction

Construction

Hose made from polypropylene fabric and films with PVC coated fabric cover, inner stainless steel & outer galvanized wire

Colour

Green with white strip

Application

For suction & discharge of various acids and alkalines

Item Code	ID		OD		WP		BR/r		W	Qty (ft)	Type	No of sections
	inch	mm	inch	mm	psi	bar	inch	mm	kg/m			
PH819-16	1	25.0	1.50	38.0	205	14	4.9	125	0.81			
PH819-20	1.1/4	32.0	1.89	48.0	205	14	5.9	150	1.06			
PH819-24	1.1/2	38.0	2.05	52.0	205	14	5.9	150	1.42			
PH819-32	2	51.0	2.52	64.0	205	14	7.9	200	1.72			
PH819-40	2.1/2	63.0	3.15	80.0	205	14	7.9	200	2.61			
PH819-48	3	76.0	3.62	92.0	205	14	11.0	280	2.96			
PH819-64	4	102.0	4.72	120.0	205	14	15.7	400	3.70			
PH819-96	6	152.0	6.89	175.0	205	14	31.5	800	11.84			
PH819-128	8	203.0	9.45	240.0	205	14	39.4	1000	14.74			
PH819-160	10	254.0	11.18	284.0	205	14	47.2	1200	20.16			



Temperature Range : Continuous: -30°C to +80°C