

PH902R - 2 SPIRALS OF HIGH TENSILE STEEL WIRE



Construction

Inner tube	Polyoxymethylene (POM)
Reinforcement	2 Spirals of high tensile steel wire
Cover	Polyamide (PA)
Application	Water blast: Heat exchanger tube cleaning. Hydraulics: Pressure test equipment (valves, tooling and control panels), hydraulic tools (instrumentation packages for gauges, control of service equipment, hydraulic jacks, hydraulic tools)

Item sfdag Code	DN	ID		OD		WP		BP		BR/r		W W
		inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	
PH902R-025	4	5/32	4.0	0.319	8.1	20300	1400	50750	3500	2.9	75	112
PH902R-03	5	3/16	4.9	0.374	9.5	20300	1400	50750	3500	3.7	95	148
PH902R-04	6	1/4	6.3	0.457	11.6	15950	1100	39875	2750	4.3	110	175

WJTA-IMCA Color Coding Scheme for Pressure Hoses - Maximum Working Pressure Applicable

					
10,000 PSI / 690 Bar	15,000 PSI / 1034 Bar	20,000 PSI / 1379 Bar	30,000 PSI / 2068 Bar	40,000 PSI / 2758 Bar	55,000 PSI / 3792 Bar



Temperature Range : Continuous : -30°C to +70°C