

PH906RR - 6 SPIRALS OF HIGH TENSILE STEEL WIRE



Construction

Inner tube	Polyoxymethylene (POM)
Reinforcement	6 Spirals of high tensile steel wire
Cover	Polyamide (PA)
Application	Water blast: Heat exchanger tube cleaning, surface preparation (concrete removal, surface cleaning of the buildings, paint removal), tank and vessel cleaning, ultra high-pressure water jet cutting and hydro demolition (cutting and demolition of armoured concrete, pipelines, paper or steel) Hydraulics: Pressure test equipment (valves, tooling and control panels)

Item sfdag Code	DN	ID		OD		WP		BP		BR/r		W
		inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH906RR-05	8	5/16	7.6	0.760	19.3	40600	2800	101500	7000	11.8	300	1055

WJTA-IMCA Color Coding Scheme for Pressure Hoses - Maximum Working Pressure Applicable

10,000 PSI / 690 Bar	15,000 PSI / 1034 Bar	20,000 PSI / 1379 Bar	30,000 PSI / 2068 Bar	40,000 PSI / 2758 Bar	55,000 PSI / 3792 Bar



Temperature Range : Continuous : -30°C to +70°C