

PH906RR - 6 SPIRALS OF HIGH TENSILE STEEL WIRE



Construction

Inner tube Polyoxymethylene (POM)

Reinforcement 6 Spirals of high tensile steel wire

Cover Polyamide (PA)

Application Water blast: Heat exchanger tube cleaning, surface preparation (concrete removal, surface

cleaning of the buildings, paint removal), tank and vessel cleaning, ultra high-pressure water jet cutting and hydro demolition (cutting and demolition of armoured concrete, pipelines, paper or

steel) Hydraulics: Pressure test equipment (valves, tooling and control panels)

Item sfdag Code	DN	ĪŌ ID		<u></u> ОВ		₩P		BP		BR/r		W w
		inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH906RR-05	8	5/16	7.6	0.760	19.3	40600	2800	101500	7000	11.8	300	1055

WJTA-IMCA Color Coding Scheme for Pressure Hoses - Maximum Working Pressure Applicable

10,000 PSI / 690 Bar 15,000 PSI / 1034 Bar 20,000 PSI / 1379 Bar 30,000 PSI / 2068 Bar 40,000 PSI / 2758 Bar 55,000 PSI / 3792 Bar

Temperature Range: Continuous: -30°C to +70°C